

TECHNICAL BULLETIN BOXCAR

60' HEAVY DUTY BOXCAR

Bulkheads for Can Stock This 100-ton boxcar has two heavy-duty moveable bulkheads and one standard moveable bulkhead for loading aluminum stock for the can manufacturing industry. Other features include end-of-car cushioning and 80,000-pound smooth steel flooring. All door type configurations are available to meet customer specifications.

DIMENSIONS (Approximate)			
Length, inside	60' 9"	Width, inside	9' 6"
Length, over couplers	68' 4 1/2"	Width, extreme	10' 7 1/2"
Height, inside	11' 1/8"	Door opening, width	16'
Height, extreme	15' 5"	Door opening, height	10' 4"
Height, top of rail to top of threshold	3' 7 15/16"	Clearance	AAR Plate C
WEIGHT / CAPACITY (Estimated)		CURVE NEGOTIABILITY RADIUS	
Light weight	96,200 lbs.	Uncoupled	180'
Gross rail load	286,000 lbs.	Coupled to like car	180'
Load limit	189,800 lbs.	Coupled to base car	229'
Cubic capacity	6,754 cu. ft.		
These general dimensions are representative and subject to change without notice as required by customer specifications or design improvements by Greenbrier.			



**From the First Mile
To the Last Mile**

